

PELICAN™

>2006 CATALOG

**WATERTIGHT
PROTECTOR™ CASES**

CASES

ANOTHER DAY AT THE OFFICE: 16,500 feet in the Solo Khumbu area of Nepal, just above Cholatse Base Camp, during filming of Rush HD's "Light of the Himalayas". Photo by David D'Angelo, Serac Adventure Films

ULTIMATE EQUIPMENT PROTECTION

For 29 years Pelican has built a reputation for manufacturing the toughest Protector™ Cases in the world. As a matter of fact, we invented the category. Over these years we've seen our cases used for some pretty crazy ideas . . . and important ones, too.

The Pelican Protector™ Case has been thrown out of helicopters in Iraq, towed along frigid fjords in Norway, and rolled over by SUVs in Tanzania. With only a few scratches to show on the outside, contents are left unscathed. Minor war wounds for major bragging rights. And that is really what it's all about. Getting your gear from point A to point B in the condition it's meant to be in: intact and functional. Because it could be that large format camera that will shoot next month's magazine cover, or a heart defibrillator that could produce results you can't put a price on.

STRONGER BY DESIGN

Pelican Protector™ Cases are made with Copolymer Polypropylene, using an open cell core and solid wall construction, which is actually stronger and lighter than the solid core wall that our competitors produce. Travel light with heavy protection. And you know it's a Pelican™ Case by the distinctive "twin-ribbed" top surface. Stainless steel pins are used for hinges and handles. The new Double-Throw latches are smarter and easier to open: it's the classic 'C' clamp design with a secondary movement that works like a pry bar to start the release and offers plenty of leverage to open with a light pull.



WATERTIGHT

The secret is the tongue-and-groove fit with a polymer o-ring acting as a waterproof seal. Also, the new Automatic Pressure Equalization Valve releases built-up air pressure while keeping water molecules out, resulting in a watertight case that is even easier to open.



EXTRA PROTECTION

Pelican's Pick 'N Pluck™ foam lets you customize the interior according to your gear. An easy, do-it-yourself system for custom-shaping the interior of the case according to your equipment. Layers of foam are pre-scored in tiny cubes. Simply measure your equipment over the grid and pluck away. Contents stay in place and get extra protection at the same time. For organizing supplies, check out our optional padded dividers. Individual compartments are adjustable using a hook and loop system. See pages 22-23 for details.



NEW

Reinforced Padlocks

Stainless steel reinforced padlock protectors provide added strength and extra security against cutting and theft.

Wheels

Stainless steel ball bearing wheels (on select cases) last longer and ride smoother. The nylon hub adjacent to the stainless steel is made to resist heat. Result: less wear and tear on the polyurethane wheel.



STAINLESS STEEL
BALL BEARING WHEELS

NYLON HUB

POLYURETHANE TIRE

PROTECTION SYSTEMS AND ELECTRONIC INSTALLATIONS



> FOR ANSWERS TO ALL YOUR OEM QUESTIONS, GO TO WWW.PELICANOEM.COM.

Seismic sensors for border patrol. \$10,000 air filters for Black Hawk helicopters. If you've got a tough OEM application, Pelican has a case for it.

Pelican OEM is a division that specializes in custom configuration. If you have sensitive or expensive equipment that needs protection, we can help.

PANEL FRAME INSERTS

This idea allows the simple attachment of an interface panel flush with the top of the case. We provide the mounting bracket which installs beneath the panel and fits against stops molded inside the case walls. A polymer o-ring seals the panel so the case remains watertight, even with the lid open. Pre-drilled holes and stainless steel screws make fabricating a custom case faster, stronger and more accurate. For information, go to PelicanOEM.com



HOT STAMPING SERVICES

Your logo can be applied in multiple colors as a decal or hot stamp, using strict PMS print controls on any Pelican Case. You'll approve a paper proof or first article prior to the run and, like everything we manufacture, our imprinting is 100% guaranteed.



SPECIALIZED APPLICATIONS

If you don't see it here, just ask. Even if we don't do it ourselves, we can probably steer you to someone who does. These ideas include solutions like waterproof bulkhead connectors for electronics or installation of internal and external components.

MAJOR PROTECTION MINIATURIZED

WATERTIGHT

The key to a watertight Micro Case is its tough polycarbonate body and the rubber liner. When closed, the lid creates a tongue-and-groove fit with the shock-absorbing rubber liner, which doubles as an o-ring. Splash it, drop it in the river. No problem. Contents are safe and dry.



The Automatic Pressure Purge Valve works on the molecular level. It uses a Gore-Tex® membrane that allows high pressure air molecules caused from altitude changes to escape. But water molecules, which are larger, are prevented from entering. The result: equalized pressure inside and outside the case, and it's easy to open. All without having to think about it.



DECISIONS, DECISIONS.

The Micro Case Series™ is available with optional Pick 'N Pluck™ foam for custom fit and extra protection for your gear.

All Micro Cases are available in four colors with solid lids or clear lids and latches with colored liners for easy identification of contents.



Black



Red



Blue




Yellow

> MICRO CASE SERIES™




1010 MICRO CASE

- Interior Dimension: $4 \frac{5}{16}'' \times 2 \frac{13}{16}'' \times 1 \frac{5}{8}''$
- Exterior Dimension: $5 \frac{7}{16}'' \times 4 \frac{1}{16}'' \times 2 \frac{1}{8}''$
- Lid/Case depth: 0.69"/0.94"
- Weight: with foam – 6.7 oz. without foam – 6.5 oz.
- Certificates: IP67




1020 MICRO CASE

- Interior Dimension: $5 \frac{1}{4}'' \times 3 \frac{1}{2}'' \times 1 \frac{5}{8}''$
- Exterior Dimension: $6 \frac{3}{8}'' \times 4 \frac{3}{4}'' \times 2 \frac{1}{8}''$
- Lid/Case depth: 0.69"/0.94"
- Weight: with foam – 8.9 oz. without foam – 8.8 oz.
- Certificates: IP67




1030 MICRO CASE

- Interior Dimension: $6 \frac{3}{8}'' \times 2 \frac{5}{8}'' \times 2''$
- Exterior Dimension: $7 \frac{1}{2}'' \times 3 \frac{7}{8}'' \times 2 \frac{7}{16}''$
- Lid/Case depth: 0.69"/1.25"
- Weight: with foam – 9.8 oz. without foam – 9.7 oz.
- Certificates: IP67, STANAG 4280



1040 MICRO CASE

- Interior Dimension: $6 \frac{7}{16}'' \times 3 \frac{13}{16}'' \times 1 \frac{11}{16}''$
- Exterior Dimension: $7 \frac{1}{2}'' \times 5 \frac{1}{16}'' \times 2 \frac{1}{8}''$
- Lid/Case depth: 0.69"/0.94"
- Weight: with foam – 11.4 oz. without foam – 11.35 oz.
- Certificates: IP67






CAT NO. 1050

CAT NO. 1060

1050

MICRO CASE


- Interior Dimension: 6 ⁷/₁₆" x 3 ¹³/₁₆" x 2 ¹¹/₁₆"
- Exterior Dimension: 7 ¹/₂" x 5 ¹/₁₆" x 3 ¹/₈"
- Lid/Case depth: 0.69"/1.94"
- Weight: with foam – 13.26 oz., without foam – 13 oz.
- Certificates: IP67



1060

MICRO CASE

- Interior Dimension: 8 ⁵/₁₆" x 4 ⁵/₁₆" x 2 ¹³/₁₆"
- Exterior Dimension: 9 ³/₈" x 5 ⁹/₁₆" x 2 ⁵/₈"
- Lid/Case depth: 0.75"/1.44"
- Weight: with foam – 1.02 lbs., without foam – 1.0 lb.
- Certificates: IP67



> SMALL CASES



CAT NO. 1120

CAT NO. 1150

CAT NO. 1200

1120

- Interior Dimension: 7 ³/₈" x 4 ⁷/₈" x 3 ¹/₁₆"
- Exterior Dimension: 8 ¹/₄" x 6 ⁹/₁₆" x 3 ⁹/₁₆"
- Lid/Case depth: 0.5"/2.5"
- Weight: with foam -1.33 lbs. without foam -1.24 lb.
- Certificates: IP67, STANAG 4280
- Single folding front handle




1150

- Interior Dimension: 8 ³/₈" x 5 ⁷/₈" x 3 ¹¹/₁₆"
- Exterior Dimension: 9 ¹/₄" x 7 ⁹/₁₆" x 4 ³/₈"
- Lid/Case depth: 0.74"/2.91"
- Weight: with foam -1.74 lbs. without foam -1.6 lbs.
- Certificates: IP67, STANAG 4280
- Single folding front handle



1200

- Interior Dimension: 9 ³/₈" x 7 ¹/₄" x 4 ¹/₁₆"
- Exterior Dimension: 10 ⁵/₈" x 9 ¹¹/₁₆" x 4 ⁷/₈"
- Lid/Case depth: 1.18"/2.9"
- Weight: with foam - 2.68 lbs. without foam -2.46 lbs.
- Certificates: IP67, STANAG 4280
- Single folding front handle





CAT NO. 1300

CAT NO. 1400

1300

- Interior Dimension: 9 ³/₈" x 7 ¹/₄" x 6 ¹/₈"
- Exterior Dimension: 10 ⁵/₈" x 9 ¹¹/₁₆" x 6 ⁷/₈"
- Lid/Case depth: 1.18"/4.9"
- Weight: with foam – 3.46 lbs.
without foam – 3.14 lbs.
- Certificates: IP67, STANAG 4280
- Single folding front handle



1400

- Interior Dimension: 10 ⁵/₈" x 9 ¹/₁₆" x 6 ⁷/₈"
- Exterior Dimension: 12 ⁵/₈" x 9 ¹¹/₁₆" x 6 ⁷/₈"
- Lid/Case depth: 1.18"/4.01"
- Weight: with foam – 4.4 lbs.
without foam – 3.9 lbs.
- Certificates: IP67, MIL-SPEC-4150J, ATA, STANAG 4280
- Single folding front handle with no-slip overmolded cushion grip



> MEDIUM CASES



1420

- Interior Dimension: 13" x 5" x 10"
- Exterior Dimension: 15" x 8 1/2" x 10 1/2"
- Lid/Case depth: 1" / 9"
- Weight: without foam - 3.87 lbs.
- Certificate: N/A
- Two boat gunwale attachment arms



1430



TOP LOADER CASE

- Available Fall 2005
- Interior Dimension: 14 3/16" x 6 3/8" x 11 1/16"
- Exterior Dimension: 16 7/8" x 8 1/16" x 13"
- Lid/Case depth: 2" / 9.69"
- Weight: with foam - 6.5 lbs.
without foam - 5.6 lbs.
- Certificate: STANAG 4280
- Unique top-load design
- Single folding top handle with no-slip overmolded cushion grip



1450

- Interior Dimension: 14 13/16" x 10 3/8" x 6"
- Exterior Dimension: 16" x 13" x 6 7/8"
- Lid/Case depth: 1.73" / 4.25"
- Weight: with foam - 6.77 lbs.
without foam - 6.03 lbs.
- Certificates: IP67, MIL-SPEC-4150J, ATA, STANAG 4280
- Single folding front handle with no-slip overmolded cushion grip





CAT NO. 1450

CAT NO. 1490

CAT NO. 1470

1470

LAPTOP CASE

- Interior Dimension: 15³/₄" x 10⁹/₁₆" x 3³/₄"
- Exterior Dimension: 16¹/₁₆" x 13¹/₁₆" x 4³/₈"
- Lid/Case depth: 1.37"/2.36"
- Weight: with foam – 5.52 lbs.
without foam – 4.29 lbs.
- Certificates: IP67, MIL-SPEC-4150J, STANAG 4280
- Lock and keys included
- Single folding front handle with no-slip overmolded cushion grip



1490

LAPTOP CASE

- Interior Dimension: 17⁷/₈" x 11¹/₂" x 4¹/₈"
- Exterior Dimension: 19⁷/₁₆" x 13¹⁵/₁₆" x 4¹/₁₆"
- Lid/Case depth: 1.49"/2.59"
- Weight: with foam – 6.5 lbs.
without foam – 5.46 lbs.
- Certificates: IP57, STANAG 4280
- Lock and keys included
- Single folding front handle with no-slip overmolded cushion grip



1495

17" LAPTOP CASE

Coming
Mid
2006

> MEDIUM CASES



CAT NO. 1510

CAT NO. 1500


1500

- Interior Dimension: 17" x 11 ¹/₁₆" x 6 ¹/₈"
- Exterior Dimension: 18 ¹/₂" x 14 ¹/₁₆" x 6 ¹⁵/₁₆"
- Lid/Case depth: 1.81"/4.3"
- Weight: with foam-7.78 lbs.
without foam-6.87 lbs.
- Certificates: IP67, MIL-SPEC-4150J, ATA, STANAG 4280
- Single folding front handle with no-slip overmolded cushion grip



1510


- Interior Dimension: 20 ³/₁₆" x 11 ³/₈" x 7 ¹/₂"
- Exterior Dimension: 22" x 14" x 9"
- Lid/Case depth: 1.79"/5.79"
- Weight: with foam- 13.6 lbs.
without foam-12 lbs.
- Certificate: STANAG 4280
- One front and one side folding handle with no-slip overmolded cushion grips
- Extendable handle with exterior mounted urethane wheels






1520

- Interior Dimension: 17 ⁷/₈" x 12 ³/₄" x 6 ³/₄"
- Exterior Dimension: 19 ¹/₈" x 15 ⁷/₁₆" x 7 ⁹/₁₆"
- Lid/Case depth: 1.81"/4.92"
- Weight: with foam – 9.35 lbs.
without foam – 8.29 lbs.
- Certificates: IP67, MIL-SPEC-4150J, ATA, STANAG 4280
- Single folding front handle with no-slip overmolded cushion grip



1550

- Interior Dimension: 18 ³/₄" x 14 ³/₈" x 7 ⁵/₈"
- Exterior Dimension: 20 ⁵/₈" x 16 ⁷/₈" x 8 ¹/₈"
- Lid/Case depth: 1.81"/5.9"
- Weight: with foam – 11.5 lbs.
without foam – 9.74 lbs.
- Certificates: IP67, MIL-SPEC-4150J, ATA, STANAG 4280
- Single folding front handle with no-slip overmolded cushion grip





CAT NO. 1560



CAT NO. 1600


1560

- Interior Dimension: 20 ³/₈" x 15 ¹/₁₆" x 9"
- Exterior Dimension: 22 ¹/₁₆" x 17 ¹⁵/₁₆" x 10 ⁷/₁₆"
- Lid/Case depth: 2" / 7"
- Weight: with foam -18.5 lbs.
without foam -16 lbs.
- Certificate: STANAG 4280
- One front and one side folding handle with no-slip overmolded cushion grips
- Extendable handle with exterior mounted urethane wheels



1600

- Interior Dimension: 21 ³/₄" x 16 ¹³/₁₆" x 7 ⁷/₈"
- Exterior Dimension: 24 ¹/₄" x 19 ⁷/₁₆" x 8 ¹¹/₁₆"
- Lid/Case depth: 1.81" / 6.1"
- Weight: with foam -13.6 lbs.
without foam -11.4 lbs.
- Certificates: IP67, MIL-SPEC-4150J, ATA, STANAG 4280
- Single folding front handle with no-slip overmolded cushion grip





CAT NO. 1610

CAT NO. 1620

1610

- Interior Dimension: 22 ³/₁₆" x 17 ¹/₈" x 10 ¹/₈"
- Exterior Dimension: 24 ⁹/₁₆" x 19 ⁵/₁₆" x 11 ¹⁵/₁₆"
- Lid/Case depth: 2"/8.5"
- Weight: with foam – 23.5 lbs.
without foam – 20 lbs.
- Certificates: IP66, STANAG 4280
- One front and two side folding handles
- Extendable handle with exterior mounted urethane wheels



1620

- Interior Dimension: 22 ¹/₁₆" x 17" x 12 ⁹/₁₆"
- Exterior Dimension: 24 ¹³/₁₆" x 19 ³/₈" x 13 ⁷/₈"
- Lid/Case depth: 1.88"/10.5"
- Weight: with foam – 24.3 lbs.
without foam – 20.5 lbs.
- Certificates: IP66, MIL-SPEC-4150J, STANAG 4280
- One front and two side folding handles
- Extendable handle with exterior mounted urethane wheels



> BIG CASES



CAT NO. 1650

CAT NO. 1660

1650

- Interior Dimension: 29 " x 17 7/8" x 10 1/2"
- Exterior Dimension: 30 3/4" x 20 1/2" x 11 5/8"
- Lid/Case depth: 3.5"/8.62"
- Weight: with foam - 33 lbs. without foam - 26.1 lbs.
- Certificates: IP66, MIL-SPEC-4150J, ATA, STANAG 4280
- Two side folding handles and one double-wide front handle for a two-handed grip
- Extendable handle with dual wheels on a single axle



1660

- Interior Dimension: 29 1/8" x 20 1/2" x 17 5/8"
- Exterior Dimension: 31 1/2" x 22 7/8" x 19"
- Lid/Case depth: 5"/14"
- Weight: with foam - 43.1 lbs. without foam - 34.7 lbs.
- Certificates: IP66, STANAG 4280
- Two folding side handles
- Extendable handle with dual wheels on a single axle



MOBILITY KIT

CAT NO. 0357

- Optional for 350 and 370 Cube Cases
 - Four removable casters with mounting plates
 - Pull strap and nylon carry bag included

CAT NO. 0350



NEW

CAT NO. 0340

CAT NO. 0370

0340

NEW

CUBE CASE

0350

CUBE CASE

0370

CUBE CASE


- Interior Dimension: 18" x 18" x 18"
- Exterior Dimension: 20 3/8" x 20 1/2" x 19 1/4"
- Lid/Case depth: 4"/13"
- Weight: with foam-29 lbs. without foam-24 lbs.
- Certificate: STANAG 4280
- Pre-installed wheel plates with removable casters
- Built-in tow handle
- Stackable with all cases in the Cube Series through interlocking slots on lid
- Two double-wide side handles for a two-handed grip



- Interior Dimension: 20" x 20" x 20"
- Exterior Dimension: 22 1/2" x 22 7/16" x 21 1/4"
- Lid/Case depth: 5"/15"
- Weight: with foam-32 lbs. without foam-26.01 lbs.
- Certificates: IP67, STANAG 4280
- Optional Mobility Kit (see page 18)
- Stackable with all cases in the Cube Series through interlocking slots on lid
- Two double-wide side handles for a two-handed grip



- Interior Dimension: 24" x 24" x 24"
- Exterior Dimension: 26 1/2" x 26 1/2" x 25 1/4"
- Lid/Case depth: 5"/19"
- Weight: with foam-41 lbs. without foam- 32 lbs.
- Certificate: IP67
- Optional Mobility Kit (see page 18)
- Stackable with all cases in the Cube Series through interlocking slots on lid
- Two double-wide side handles for a two-handed grip



> **BIG CASES**



CAT NO. 1700

1700

RIFLE CASE

- Interior Dimension: 35 ³/₄" x 13 ¹/₂" x 5 ¹/₄"
- Exterior Dimension: 38 ¹/₈" x 16" x 6 ¹/₈"
- Lid/Case depth: 1.73"/3.5"
- Weight: with foam-16.6 lbs., without foam-14.4 lbs.
- Certificates: IP67, MIL-SPEC-4150J, ATA, STANAG 4280
- One stationary front handle and one folding side handle
- Stainless steel ball bearing wheels





NEW

CAT NO. 1750


CAT NO. 1720

1720

NEW

RIFLE CASE

- Interior Dimension: 42" x 13 1/2" x 5 1/4"
- Exterior Dimension: 44 3/8" x 16" x 6 1/8"
- Lid/Case depth: 1.73"/3.5"
- Weight: with foam-19.1 lbs., without foam-16.8 lbs.
- Certificate: STANAG 4280
- One folding front handle and two folding side handles
- Stainless steel ball bearing wheels



1750

RIFLE CASE

- Interior Dimension: 50 1/2" x 13 1/2" x 5 1/4"
- Exterior Dimension: 53" x 16" x 6 1/8"
- Lid/Case depth: 1.73"/3.5"
- Weight: with foam-22.3 lbs., without foam-19.5 lbs.
- Certificates: IP67, STANAG 4280
- One stationary front handle and one folding side handle
- Stainless steel ball bearing wheels



SECURE IT KEEP IT DRY AND CUSTOMIZE IT

> PICK N' PLUCK FOAM SETS

The foam in Pelican's Protector™ Cases consists of a layer of convoluted foam for the lid, a 1-inch layer to pad the bottom, and one to four layers of Pick N' Pluck™ in between. These center sections are also available separately. Here is a breakdown of what you can expect to find in each of our cases:

3-PIECE SET

- 1120 ▪ 1150 ▪ 1200
- 1300 ▪ 1400 ▪ 1490
- 1450 ▪ 1470 ▪ 1520
- 1500 ▪ 1510 ▪ 1750
- 1700 ▪ 1720



4-PIECE SET

- 1550
- 1560
- 1600
- 1650

5-PIECE SET

- 1430 ▪ 1610
- 1660 ▪ 340
- 350 ▪ 370
- 1620



6-PIECE SET

- 1620

Foam dimensions will vary with the interior dimensions of each case.

TRAVEL BAG

Bag with 1520 Case
Bag only

Cat No. 1526
Cat No. 1527



DESICCANT SILICA GEL CAT NO. 1500D

Drinks dampness and prevents condensation from trapped air when cases are opened in high humidity climates. Stops mildew before it starts. Reusable by oven drying yearly. Fits all Pelican™ Cases. 4" x 2 1/16" x 9/16"



PERSONALIZED NAME PLATE

Fill out and send in the Nameplate Services envelope included inside your Pelican™ Case and have your name engraved on a black nameplate (for a nominal fee).



PELILOCK CAT NO. 1506

4-number code combination brass lock. Fits all Pelican™ Cases.



TSA LOCK CAT NO. 1506TSA

3-number code combination TSA approved lock also works with TSA Pass Key for worry free travel. Fits all Pelican™ Cases.



> PADDED DIVIDERS / LID ORGANIZERS

PADDED DIVIDER OPTIONS (CATALOG NUMBERS)

NUMBER OF LAYERS	CASE NUMBER	PADDED DIVIDERS INCLUDED INSIDE CASE	PADDED DIVIDERS ONLY
1	1450	1454	1455
1	1500	1504	1505
1	1510	1514	1515
1	1520	1524	1525
1	1550	1554	1555
1	1560	1564	1565
1	1600	1604	1605
1	1610	1614	1615
2	1620	1624	1625
1	1650	1654	1655
1	1660	1664	1665
2	340	344	345
2	350	354	355
2	370	374	375

> PADDED DIVIDERS

Main dividers that span the length of the case are complimented by varying sizes of subdividers. Velcro® edges make it easy to reposition these dividers into the spaces you need.



The Cube Case Series includes a removable top layer with a zip-up mesh top.

1430 CASE OPTIONS

	W/ CASE	W/OUT CASE
PHOTO DIVIDER SET Two Divider Layers plus Photo Lid Organizer	1434	1435
OFFICE DIVIDER SET Office Interior plus Mesh Lid Organizer and Strap	1436	N/A
BOAT BRACKET KIT	N/A	1438


> LID ORGANIZERS

Made of leather or waterproof Ballistic Nylon with nylon zippers. Multitude of pockets in various sizes protect and keep your gear organized. Installs with Velcro® strips (included) or self tapping screws.

LID ORGANIZER




ATTACHÉ LID ORGANIZER



PHOTOGRAPHER'S ORGANIZER



COMPUTER/ATTACHÉ ORGANIZER



LID ORGANIZER OPTIONS (CATALOG NUMBERS)

CASE NUMBER	LEATHER LID ORGANIZER WITHOUT CASE	MESH LID ORGANIZER WITHOUT CASE	PHOTOGRAPHER'S LID ORGANIZER WITHOUT CASE
1430	N/A	N/A	1439
1470	1478	N/A	N/A
1490	1498	N/A	N/A
1500	N/A	1509	1508
1510	N/A	1519	N/A
1520	N/A	1509	1508
1560	N/A	1569	N/A
1600	N/A	1609	N/A
1610	N/A	1609	N/A
1620	N/A	1609	N/A
1650	N/A	1659	N/A
1660	N/A	1669	N/A
340	N/A	349	N/A
350	N/A	359	N/A
370	N/A	379	N/A

1490 CASE OPTIONS

	WITH CASE & LID ORGANIZER	WITHOUT CASE
PICK N' PLUCK™ FOAM Fits computers up to 17 3/8" x 11" x 3 3/8"	1490CC #2	1491
COMPUTER BOTTOM MOLDED FOAM INSERT Fits computers up to 14" x 10 1/8" x 2 1/2"	1490CC #1	1499C

> CASE SPECIFICATIONS

CASE	EXTERNAL DIMENSIONS (L x W x H)	INTERNAL DIMENSIONS (L x W x H)	DEPTH		WHEELS	EXTENDABLE HANDLES	WEIGHT WITH FOAM	WEIGHT WITHOUT FOAM	COLORS
			LID	CASE					
1010'	5 7/16" x 4 1/16" x 2 1/8" (13.8 x 10.3 x 5.4 cm)	4 5/16" x 2 9/16" x 1 5/8" (11.3 x 7.5 x 4.3 cm)	0.69" (1.8 cm)	0.94" (2.5 cm)	-	-	6.7 oz. (0.190 kg)	6.5 oz. (0.186 kg)	
1020'	6 3/8" x 4 3/4" x 2 1/8" (16.2 x 12.1 x 5.4 cm)	5 1/4" x 3 1/2" x 1 5/8" (13.7 x 9.2 x 4.3 cm)	0.69" (1.8 cm)	0.94" (2.5 cm)	-	-	8.9 oz. (0.253 kg)	8.8 oz. (0.250 kg)	
1030'	7 1/2" x 3 7/8" x 2 7/16" (19.1 x 9.8 x 6.2 cm)	6 3/8" x 2 5/8" x 2" (16.5 x 7.0 x 5.2 cm)	0.75" (1.9 cm)	1.25" (3.3 cm)	-	-	9.8 oz. (0.280 kg)	9.7 oz. (0.277 kg)	
1040'	7 1/2" x 5 1/16" x 2 1/8" (19.1 x 12.9 x 5.4 cm)	6 7/16" x 3 13/16" x 1 11/16" (16.7 x 10 x 4.4 cm)	0.75" (1.9 cm)	0.94" (2.5 cm)	-	-	11.4 oz. (0.326 kg)	11.35 oz. (0.322 kg)	
1050'	7 1/2" x 5 1/16" x 3 1/8" (19.1 x 12.9 x 7.9 cm)	6 7/16" x 3 9/16" x 2 11/16" (16.7 x 10 x 7.0 cm)	0.75" (1.9 cm)	1.94" (4.9 cm)	-	-	13.26 oz. (0.376 kg)	13 oz. (0.372 kg)	
1060'	9 3/8" x 5 9/16" x 2 5/8" (23.8 x 14.1 x 6.7 cm)	8 5/16" x 4 5/16" x 2 13/16" (21.4 x 11.3 x 5.7 cm)	0.75" (1.9 cm)	1.44" (3.7 cm)	-	-	1.02 lb. (0.463 kg)	1.0 lb. (0.459 kg)	
1120"	8 1/4" x 6 9/16" x 3 9/16" (20.9 x 16.6 x 9 cm)	7 3/8" x 4 7/8" x 3 1/16" (18.7 x 12.4 x 7.8 cm)	0.5" (1.3 cm)	2.5" (6.5 cm)	-	-	1.33 lb. (0.6 kg)	1.24 lb. (0.5 kg)	
1150"	9 1/4" x 7 9/16" x 4 3/8" (23.5 x 19.2 x 11.1 cm)	8 3/8" x 5 7/8" x 3 11/16" (21.2 x 14.9 x 9.3 cm)	0.74" (1.9 cm)	2.91" (7.4 cm)	-	-	1.74 lb. (0.9 kg)	1.60 lb. (0.8 kg)	
1200"	10 5/8" x 9 11/16" x 4 7/8" (27 x 24.6 x 12.4 cm)	9 3/8" x 7 1/4" x 4 1/16" (23.8 x 18.4 x 10.3 cm)	1.18" (3 cm)	2.9" (7.5 cm)	-	-	2.68 lb. (1.3 kg)	2.46 lb. (1.2 kg)	
1300"	10 5/8" x 9 11/16" x 6 7/8" (27 x 24.6 x 17.5 cm)	9 3/8" x 7 1/4" x 6 1/8" (23.8 x 18.4 x 15.5 cm)	1.18" (3 cm)	4.9" (12.5 cm)	-	-	3.46 lb. (1.6 kg)	3.14 lb. (1.4 kg)	
1400"	12 5/8" x 9 11/16" x 6 7/8" (34 x 29.5 x 15.2 cm)	10 5/8" x 9 1/16" x 5 3/16" (23.8 x 18.4 x 15.5 cm)	1.18" (3 cm)	4.01" (10.2 cm)	-	-	4.4 lb. (2.0 kg)	3.9 lb. (1.8 kg)	
1420"	15" x 8 1/2" x 10 1/2" (38.1 x 21.6 x 26.7 cm)	13" x 5" x 10" (33 x 12.7 x 25.4 cm)	1.0" (2.5 cm)	9.0" (22.8 cm)	-	-	N/A	3.87 lb. (1.7 kg)	
1430"	16 7/8" x 8 11/16" x 13" (42.9 x 22.1 x 32.5 cm)	14 3/16" x 6 3/8" x 11 11/16" (36 x 16.2 x 29.7 cm)	2.0" (5.1 cm)	9.69" (24.6 cm)	-	-	6.5 lb. (2.95 kg)	5.6 lb. (2.55 kg)	
1450"	16" x 13" x 6 7/8" (40.6 x 33 x 17.4 cm)	14 13/16" x 10 3/8" x 6" (37.6 x 26.3 x 15.2 cm)	1.73" (4.4 cm)	4.25" (10.8 cm)	-	-	6.77 lb. (2.9 kg)	6.03 lb. (2.5 kg)	
1470"	16 11/16" x 13 1/16" x 4 3/8" (42.4 x 33.2 x 11.1 cm)	15 3/4" x 10 9/16" x 3 1/4" (40 x 26.8 x 9.5 cm)	1.37" (3.5 cm)	2.36" (6 cm)	-	-	5.52 lb. (2.5 kg)	4.29 lb. (1.7 kg)	
1490"	19 7/16" x 13 13/16" x 4 11/16" (49.4 x 35.4 x 11.9 cm)	17 7/8" x 11 1/2" x 4 1/8" (45.4 x 29.2 x 10.5 cm)	1.49" (3.8 cm)	2.59" (6.6 cm)	-	-	6.5 lb. (2.7 kg)	5.46 lb. (2.3 kg)	
1500"	18 1/2" x 14 1/16" x 6 15/16" (47 x 35.7 x 17.6 cm)	17" x 11 7/16" x 6 1/8" (43.2 x 29 x 15.5 cm)	1.81" (4.6 cm)	4.3" (11 cm)	-	-	7.78 lb. (3.2 kg)	6.87 lb. (2.9 kg)	
1510"	22" x 14" x 9" (55.9 x 35.1 x 22.9 cm)	20 3/16" x 11 3/8" x 7 1/2" (51.4 x 28.9 x 19.2 cm)	1.79" (4.6 cm)	5.79" (14.7 cm)	Yes	Yes	13.6 lb. (6.21 kg)	12 lb. (5.55 kg)	
1520"	19 1/8" x 15 7/16" x 7 9/16" (48.6 x 39.2 x 19.2 cm)	17 7/8" x 12 3/4" x 6 3/4" (45.4 x 32.4 x 17.1 cm)	1.81" (4.6 cm)	4.92" (12.5 cm)	-	-	9.35 lb. (3.9 kg)	8.29 lb. (3.6 kg)	
1550"	20 5/8" x 16 7/8" x 8 1/8" (52.5 x 43.7 x 21.7 cm)	18 3/4" x 14 3/8" x 7 5/8" (48.1 x 26.7 x 19.7 cm)	1.81" (4.6 cm)	5.9" (15 cm)	-	-	11.5 lb. (5.4 kg)	9.74 lb. (4.8 kg)	
1560"	22 1/16" x 17 15/16" x 10 7/16" (56 x 45.5 x 26.4 cm)	20 3/8" x 15 7/16" x 9" (51.8 x 39.2 x 22.9 cm)	2.0" (5.1 cm)	7.0" (17.7 cm)	Yes	Yes	18.5 lb. (9.07 kg)	16 lb. (7.71 kg)	
1600"	24 1/4" x 19 7/16" x 8 11/16" (61.6 x 49.4 x 22 cm)	21 3/4" x 16 13/16" x 7 7/8" (55.2 x 42.7 x 20 cm)	1.81" (4.6 cm)	6.1" (15.5 cm)	-	-	13.6 lb. (6.4 kg)	11.4 lb. (5.9 kg)	
1610"	24 9/16" x 19 5/16" x 11 15/16" (62.4 x 49 x 30.2 cm)	22 3/16" x 17 1/8" x 10 1/8" (56.3 x 43.5 x 26.9 cm)	2.0" (5.2 cm)	8.5" (21.6 cm)	Yes	Yes	23.5 lb. (10.2 kg)	20 lb. (9.1 kg)	
1620"	24 13/16" x 19 3/8" x 13 7/8" (63 x 49.2 x 35.2 cm)	22 1/16" x 17" x 12 9/16" (56 x 43.2 x 32 cm)	1.88" (4.8 cm)	10.5" (26.7 cm)	Yes	Yes	24.3 lb. (11.8 kg)	20.5 lb. (11.1 kg)	
1650"	30 3/4" x 20 1/2" x 11 5/8" (78.1 x 52 x 29.5 cm)	29 " x 17 7/8" x 10 1/2" (73.6 x 45.4 x 26.7 cm)	3.5" (8.9 cm)	8.62" (21.9 cm)	Yes	Yes	33 lb. (15 kg)	26.1 lb. (13.2 kg)	
1660"	31 1/2" x 22 7/8" x 19" (80 x 58.1 x 47.9 cm)	29 1/8" x 20 1/2" x 17 5/8" (74 x 52.5 x 44.8 cm)	5" (12.7 cm)	14" (35.8 cm)	Yes	Yes	43.1 lb. (19.1 kg)	34.7 lb. (15.5 kg)	
0340"	20 3/8" x 20 1/2" x 19 1/4" (51.8 x 52.1 x 49.9 cm)	18" x 18" x 18" (45.7 x 45.7 x 45.7 cm)	4" (10.2 cm)	13" (33.0 cm)	Yes	Yes	29 lb. (13.15 kg)	24 lb. (10.89 kg)	
0350"	22 1/2" x 22 7/16" x 21 1/4" (57.1 x 57.1 x 54 cm)	20" x 20" x 20" (50.8 x 50.8 x 50.8 cm)	5.0" (12.7 cm)	15" (38.1 cm)	Optional	-	32 lb. (14.5 kg)	26.01 lb. (11.8 kg)	
0370"	26 1/2" x 26 1/2" x 25 1/4" (67.3 x 67.3 x 64.1 cm)	24" x 24" x 24" (61 x 61 x 61 cm)	5.0" (12.7 cm)	19" (48.3 cm)	Optional	-	41 lb. (18.6 kg)	32 lb. (14.5 kg)	
1700"	38 1/8" x 16" x 6 1/8" (96.8 x 45.2 x 15.5 cm)	35 3/4" x 13 1/2" x 5 1/4" (91 x 35.1 x 13.3 cm)	1.73" (4.4 cm)	3.5" (8.9 cm)	Yes	-	16.6 lb. (8.9 kg)	14.4 lb. (6.6 kg)	
1720"	44 3/8" x 16" x 6 1/8" (112.7 x 40.6 x 15.6 cm)	42 " x 13 1/2" x 5 1/4" (106.7 x 34.3 x 13.3 cm)	1.73" (4.4 cm)	3.5" (8.9 cm)	Yes	-	19.1 lb. (8.7 kg)	16.8 lb. (7.6 kg)	
1750"	53" x 16" x 6 1/8" (134.6 x 44.3 x 15.4 cm)	50 1/2" x 13 1/2" x 5 1/4" (128.3 x 34.1 x 13.3 cm)	1.73" (4.4 cm)	3.5" (8.9 cm)	Yes	-	22.3 lb. (11.6 kg)	19.5 lb. (10.7 kg)	

All Pelican Cases have a 2 degree Draft Angle with a Bottom Radius of 0.66 +/- 0.020. Length and Width are measured at the center line of the case at a level where the top of the panel frame would be positioned. Depth is measured at the center of the case and includes lid depth.

BUOYANCY MAXIMUM	RANGE TEMPERATURE MINIMUM/MAXIMUM	OPTIONAL ACCESSORIES (CATALOG NUMBERS)						CERTIFICATES	CASE
		FOAM	PADDED DIVIDERS	PANEL FRAMES	LID ORGANIZERS	MOBILITY KIT	NAMEPLATE		
8.0 oz. (0.190 kg)	-10 / 200 °F (-23 / 93 °C)	1012	-	-	-	-	-	IP67	1010"
12 oz. (0.340 kg)	-10 / 200 °F (-23 / 93 °C)	1022	-	-	-	-	-	IP67	1020"
1.0 lb. (0.454 kg)	-10 / 200 °F (-23 / 93 °C)	1032	-	-	-	-	-	IP67	1030"
1.25 lb. (0.560 kg)	-10 / 200 °F (-23 / 93 °C)	1042	-	-	-	-	-	IP67	1040"
1.75 lb. (0.800 kg)	-10 / 200 °F (-23 / 93 °C)	1052	-	-	-	-	-	IP67	1050"
2.5 lb. (0.134 kg)	-10 / 200 °F (-23 / 93 °C)	1062	-	-	-	-	-	IP67	1060"
5.0 lb. (2.3 kg)	-10 / 200 °F (-23 / 93 °C)	1121	-	1120PF	-	-	-	IP67, STANAG 4280	1120"
8.1 lb. (3.7 kg)	-10 / 200 °F (-23 / 93 °C)	1151	-	1150PF	-	-	-	IP67, STANAG 4280	1150"
12.5 lb. (5.4 kg)	-10 / 210 °F (-23 / 99 °C)	1201	-	1200PF	-	-	-	IP67, STANAG 4280	1200"
11.9 lb. (5.4 kg)	-10 / 210 °F (-23 / 99 °C)	1301	-	1300PF	-	-	-	IP67, STANAG 4280	1300"
24 lb. (9.1 kg)	-10 / 210 °F (-23 / 99 °C)	1401	-	1400PF	-	-	Optional	IP67, MIL-SPEC-4150J, ATA, STANAG 4280	1400"
20 lb. (9.07 kg)	-10 / 210 °F (-23 / 99 °C)	1421	-	1420PF	-	-	-	-	1420"
59 lb. (27.1 kg)	-10 / 210 °F (-23 / 99 °C)	1431	1435-Photo 1436-Office	1430PF	1439	-	Optional	STANAG 4280	1430"
25 lb. (11.3 kg)	-10 / 210 °F (-23 / 99 °C)	1451	1455	1450PF	-	-	Optional	IP67, MIL-SPEC-4150J, STANAG 4280	1450"
30.7 lb. (13.6 kg)	-10 / 210 °F (-23 / 99 °C)	1471	-	-	-	-	Optional	IP67, MIL-SPEC-4150J	1470"
41 lb. (18.1 kg)	-10 / 210 °F (-23 / 99 °C)	1491	-	1490PF	1498	-	Optional	IP57, STANAG 4280	1490"
51 lb. (22.7 kg)	-10 / 210 °F (-23 / 99 °C)	1501	1505	1500PF	1508 \ 1509	-	Optional	IP67, MIL-SPEC-4150J, ATA, STANAG 4280	1500"
64.2 lb. (29.1 kg)	-10 / 210 °F (-23 / 99 °C)	1511	1515	-	1519	-	Optional	STANAG 4280	1510"
40 lb. (18.1 kg)	-10 / 210 °F (-23 / 99 °C)	1521	1525	1520PF	1508 \ 1509	-	Optional	IP67, MIL-SPEC-4150J, ATA, STANAG 4280	1520"
70 lb. (31.8 kg)	-10 / 210 °F (-23 / 99 °C)	1551	1555	1550PF	-	-	Optional	IP67, MIL-SPEC-4150J, ATA, STANAG 4280	1550"
104 lb. (41.2 kg)	-10 / 210 °F (-23 / 99 °C)	1561	1565	-	-	-	Optional	STANAG 4280	1560"
75 lb. (34 kg)	-10 / 210 °F (-23 / 99 °C)	1601	1605	-	1609	-	Optional	IP67, MIL-SPEC-4150J, ATA, STANAG 4280	1600"
120 lb. (54.4 kg)	-10 / 210 °F (-23 / 99 °C)	1611	1615	-	1609	-	Optional	IP66, STANAG 4280	1610"
150 lb. (68 kg)	-10 / 210 °F (-23 / 99 °C)	1621	1625	-	1609	-	Optional	IP66, MIL-SPEC-4150J, STANAG 4280	1620"
181 lb. (82.1 kg)	-10 / 210 °F (-23 / 99 °C)	1651	1655	-	1659	-	Optional	IP66, MIL-SPEC-4150J, ATA, STANAG 4280	1650"
158.8 lb. (158.8 kg)	-10 / 210 °F (-23 / 99 °C)	1661	1665	-	1669	-	Optional	IP66, STANAG 4280	1660"
220 lb. (99.8 kg)	-10 / 210 °F (-23 / 99 °C)	0341	0345	-	0349	Included	Optional	STANAG 4280	0340"
270 lb. (122 kg)	-10 / 210 °F (-23 / 99 °C)	0351	0355	-	0359	0357	Optional	IP67, STANAG 4280	0350"
465 lb. (211 kg)	-10 / 210 °F (-23 / 99 °C)	0371	0375	-	0379	0357	Optional	IP67, STANAG 4280	0370"
137 lb. (62.1 kg)	-10 / 210 °F (-23 / 99 °C)	1701	-	-	-	-	Optional	IP67, MIL-SPEC-4150J, STANAG 4280	1700"
160 lb. (72.6 kg)	-10 / 210 °F (-23 / 99 °C)	1721	-	-	-	-	Optional	STANAG 4280	1720"
187 lb. (84.8 kg)	-10 / 210 °F (-23 / 99 °C)	1751	-	-	-	-	Optional	IP67, STANAG 4280	1750"



23215 Early Avenue • Torrance, CA 90505 USA
Tel 310.326.4700 • 800.473.5422 (Outside CA)
Fax 310.326.3311 • www.pelican.com

PELICAN PRODUCTS, CANADA
10221-184th St. • Edmonton, Alberta T5S 2J4
Tel 780.481.6076 • Fax 780.481.9586
www.pelicanproducts.ca

PELI PRODUCTS, S.A. (Europe)
c/ Casp, 33-B Pral. • 08010 • Barcelona, Spain
Tel 34.93.467.4999 • Fax 34.93.487.7393
www.peli.com

PELICAN PRODUCTS K.K.
Suntec Bldg. 7F • 2-2-7 Honcho, Funabashi-shi
Chiba 273-0005 Japan
Tel +81(0)47.433.7715 • Fax +81.(0)47.433.7882
www.pelicanproducts.jp

**THE PELICAN UNCONDITIONAL
LIFETIME GUARANTEE**

©2005 Pelican Products, Inc. All trademarks and logos displayed herein are registered and unregistered trademarks of Pelican Products, Inc. and others. iPod is a registered trademark of Apple Computer, Inc. Gore-Tex is a trademark of W.L. Gore & Associates. Velcro is a registered trademark of Velcro Industries B.V.
Part. No. 0030-000-300 AU/05